

COR-HD80V

1080p (1920 x 1080) SDI OUTDOOR IR BULLET CAMERA

1080P
HD CCTV



SPECIFICATIONS

Video Sensor	1/3" Panasonic 2.1 Megapixel CMOS
Lens	2.8mm - 12mm Megapixel Rated Varifocal
Effective Pixels	1944(H) x 1092 (V)
IR range	90-120 feet /27-37 meters
IR LED	60IR
Video Output	HD-SDI 1080P BNC
Electronic Shutter	AUTO/ MANUAL /FLK
Scanning System	Progressive Scan
Minimum Illumination	0.2 LUX (Color/Day) 0.01 LUX (B/W)
3D-DNR	OFF / ON (LOW/MIDDLE/HIGH)
WDR	OFF / ON (Level Adjustable) (Long and short exposure)
OSD	Yes
Sens-Up	OFF / ON
White Balance	AWB/ ATW / PUSH / MANUAL
Back Light Control	OFF / ON
D-ZOOM	1.0x - 8.0x
TV System	NTSC
Defog	OFF / ON
Power Consumption	600mA
Working Temperature	-10°~ to 50°C / -14° +122 °F
Power	12V DC
Dimension(D) (H)	7.87 " x 4.72 " (inches) / 200 x 120 (mm)
Weight	1.32 (lb) / 0.6 (kg)

Additional OSD Options:

Exposure-wb-manual-special-cam-title-motion-privacy-park-line-image-adj-comm-adj-language-area-state-height-width-mirror-front-contrast-sharpness

KEY BENEFITS

- DIGITAL 1080P HIGH DEFINITION OVER COAX
- DSP EYENIX EN772A
- TAMPERPROOF LENS
- 2.8-10MM VARIFOCAL MEGAPIXEL LENS
- INTUITIVE OSD MENU
- DIGITAL DEFOG

Designed with high quality in mind, the HD5V is perfect for industrial applications where image adjusting is vital. Dual scan true wide dynamic range allows for the best picture in a number of bright lighting condition. The high power infrared system is crucial for capturing images on a pitch black night. **A high-end chipset makes all the difference, don't be fooled by cheap look-alikes.**

- Improved heavy gauge cable harness
- Heavy tamperproof bracket
- No glare, focus shift prevention
- 6 Point quality control system

Tamperproof lens adjustment system



Elbow joint has interlocking teeth to prevent slippage



COR-HD80V

