COR-RAPPIX8G2
8CH 1080P HD-SDI / ANALOG HYBRID DVR

14.9"

2.83"

MADE IN KOREA

FULL HD 1080P

DIGITAL

KEY BENEFITS

- 1080P / ANALOG HYBRID DVR
- INDIVIDUAL SMART AUTO-SENSING INPUTS
- INDIVIDUAL CHANNEL OPERATION
- 2 LEVELS OF FREE CMS TO CHOOSE FROM
- DIGITAL ZOOM LIVE OR PLAYBACK
- FEATURE RICH SMART PHONE APP
- 8CH SYNCHRONIZED SIMULTANEOUS PLAYBACK

Make an upgrade with ease. When clients need the best HD but are still on tight budgetary restrictions, the RappixG2 delivers. It is perfect for smart phone / tablet viewing and multiple resolution formats (SDI 1080P & 720P / Analog & 960H). The digital pinch/ zoom functions are easy to use while live and playback modes are intuitive for end users. Truly an amazing price for a Korean made system.

SPECIFICATIONS	
* DEVICE	
Compression	H.264
Recording	1080P @ 15ips = 120fps Analog & 960H @ 30ips = 240fps
Playback	1920 x 1080p full HD
OSD	Graphic User Interface (Multilingual)
* HARDWARE	
Video Input Format	HD-SDI / 960H / SD Analog
Video Input	8 CH BNC
Video Output	1 HDMI (1920 x 1080P) / 1 VGA / 1 Composite BNC / SPOT
Audio Input	4 Inputs (RCA)
Audio Output	1 Output (RCA)
Ethernet	1 Port (10 / 100 Mbps / 1 Gbps Ethernet (RJ-45))
Protocol	TCP/IP, HTTP, DHCP, ADSL(PPPoE)
PTZ Control	1 Port (RS-485 Terminal Block)
Alarm In / Out	4 NO / NC / 1 Relay
USB	2 Ports (1 x Front Panel, 1 x Rear Panel)
Storage	2 HDDS (up to 4TB each)
* SOFTWARE	
Recording Scheduling	Fully Programmable (by Weekday / by Hour / by Camera / by Continuous + Event + PreEvent)
Network	10/100 Base-T
Recording Quality	Best / High / Moderate / Economic
Recording Mode	Continuous / Alarm / Motion / Manual
Pre-Event	Up to 20 minutes
Motion Detection	Region Selection (Mouse Drag)
Playback Speed	x0.25, x0.5, x2, x4, x8, x16, x32, x64
Backup Format	BMP, AVI, Proprietary Format
Backup Devices	USB / External HDD, Network
Menu	User Friendly GUI
Features	Digital Zoom, Network Time Protocol, S.M.A.R.T, Multi-Language, E-mail Notification
DDNS	Built-in
Emergency Recording	Yes
CMS	Single / Multi-Client and CMS
Mobile Support	iOS / Android
Operating System	Embedded Linux
* POWER	
Operating Temperature	41°F~104°F / 5°C~40°C
Operating Humidity	0% ~ 90%
Power requirement	DC 12V, 6.67A external adapter
* PHYSICAL	
Dimensions (W x D x H)	14.9" x 13.28" x 2.83" / 380mm x 340mm x 72mm
Weight	9.2 pounds / 4.1 kg (without HDD)

COR-RAPPIX4G2

Android Compatible

iOS Compatible

Front Panel

Rear Panel

IR Remote Control

USB Mouse

Free CMS software

CORTEX®